

# Firstek Scientific

## Bath

# Cooling Circulator



- CFC free refrigerants
- All units capable of heating and refrigeration applications
- Safety: Over temperature cut-out with thermal fuse

### Specifications:

| MODEL                      | B401L/B401H                         | B402L/B402H                 | B403L/B403H                 |
|----------------------------|-------------------------------------|-----------------------------|-----------------------------|
| Temperature                |                                     |                             |                             |
| Working range              | -20°C ~ 100°C / 0°C ~ 100°C         | -20°C ~ 100°C / 0°C ~ 100°C | -20°C ~ 100°C / 0°C ~ 100°C |
| Stability                  | ± 0.1°C                             | ± 0.1°C                     | ± 0.1°C                     |
| Setting & readout          | Digital                             | Digital                     | Digital                     |
| Heater                     | 1KW                                 | 1KW                         | 1.5KW                       |
| Cooling Capacity (at 20°C) | 600 Kcal/hr                         | 750 Kcal/hr                 | 1500 Kcal/hr                |
| Stirring                   | By built-in Circulating Pump        |                             |                             |
| Pumping flow               | 7 Liters/min. 0.2Kg/cm <sup>2</sup> |                             |                             |
| Dimension                  |                                     |                             |                             |
| Lid opening                | W11.5xD10cm                         | W15xD15cm                   | W20xD23cm                   |
| Reservoir                  | W16xD28xH15cm                       | W21xD31xH17cm               | W22xD41xH22cm               |
| Capacity                   | 6.7 Liters                          | 11.7 Liters                 | 20 Liters                   |
| Overall                    | W27xD43xH57cm                       | W30.5xD46.5xH60cm           | W33xD56xH75cm(含輪子)          |
| Power source               | 110/220V 60/50Hz<br>14/7A           | 110/220V 60/50Hz<br>14/7A   | 220V 60/50Hz<br>8A          |